



Notes :
 3. Building numbers at the arrow to be omitted if no building in the arrow direction from the plate to the start / end of the street.

- Notes :
1. Specification of street name plates:
 - Plate dimension
 - Height : 324mm.
 - Corners : 25mm radius.
 - Thickness : 3mm.
 - Length (L) : 750mm to 2000mm, with 50mm increments (Depending on length of letters & characters).
 - Dimensions and types of letters & characters
 - Letters : Transport Medium, 70mm (H) for capital letters, 50mm (H) for small letters and 50mm (H) for building number numerals.
 - Characters : Avector Chinese True Type Fonts (Hong Kong) - BlackBold, 全真字庫 (港人版) - 粗黑, 98mm high.
 - Colours
 - Background : White.
 - Characters & letters : Black.
 - Border : Black.
 - Material
 - Aluminium plates : 3mm thick, Temper H14, AW-1200, as per BS EN 485-2:2016+A1:2018.
 - Visibility characteristics : Class CR2 daylight chromaticity and luminance factors; and Class RA1 coefficient of retroreflection as per BS EN 12899-1:2007.
 - Characters & letters : Screen-printing ink compatible with the reflective sheeting, or cut out from non-reflective adhesive sheeting.
 2. Single arrow to be used at start and end of a street, and double arrows to be used at all other locations of the street.

D	Note 1 updated.		Nov 22
C	Note 1 updated.	-	Mar 18
B	Note 1 updated.	-	Nov 07
A	Border widths revised.	-	Mar 05
	New Issue	-	Mar 04
REF.	REVISION	SIGNATURE	DATE

STREET NAME PLATE WITH BUILDING NUMBERS

HIGHWAYS DEPARTMENT

REFERENCE	DRAWING No.	CAD
SCALE	H 2206D	
DIAGRAMMATIC		