

Gully grating			Corresponding kerb overflow weir			
Type	Size (mm)	Drg. no.	Type		Kerb type	Drg. no.
			Horizontal Slots	Vertical Slots		
GA1 - 450	Double triangular 517 x 432	H3116 H3117 H3118B	K1-450H	K1-450V	K1	H 3121 H 3123A
			K2-450H	K2-450V	K2	H 3125 H 3126A
			PR-450H	PR-450V	Conc. barrier	H 3127 H 3128/1
			N/A	PRS-450V	Conc. barrier at sag sections of expressway	H 3128/2
GA2 - 325	Rectangular 447 x 325	H3119 H3120	K3-325H	K3-325V	K3	H 3122 H 3124A
			PR-325H	PR-325V	Conc. barrier	H 3127 H 3128/1
			N/A	PRS-325V	Conc. barrier at sag sections of expressway	H 3128/2

Notes :

1. Refer to RD/GN/035 and its associated supplementary guidance / guidelines to determine if weir is required at a particular location, and, if required, which type of weir (with horizontal or vertical slots) should be used.
2. For details of kerbs refer to drg. no. H1118.
3. GA2-325 gullies can be used for highway structures and cycle tracks as necessary.

C	Notes 1 revised PRS-450V, PRS-325V added	Original signed	Sep 15
B	Information in Note 1 updated	-	Oct 13
A	Inclusion of cycle tracks in Note 3	-	May 10
	Former drg. no. H3001/2 with general revision	-	June 94
REF.	REVISION	SIGNATURE	DATE

REFERENCE TABLE FOR DIFFERENT
TYPES OF GULLY GRATINGS AND
KERB OVERFLOW WEIRS

HIGHWAYS DEPARTMENT

REFERENCE

DRAWING No.

CAD

SCALE

H 3104C