Note 1 to Note 9 Applicable to both drawing nos. H6133 and H6138:

- 1. All dimensions are in millimetres.
- 2. Colour of painting to BS 5252F (1976):
 - (a) Logo: Red, Code 04E53
 - (b) Letters, characters & lines : Black, Code 00E53
 - (c) Other: Yellow, Code 08E51
- The face of the board shall be constructed in retroreflective materials conforming to "Class RA1" of BS EN 12899-1.
- 4. The board shall be made of 3mm thick aluminium backing plate conforming to BS EN485.
- 5. For details of Highways Department's logo, refer to drawing no. H6101.
- 6. For details of cartoon figure, refer to drawing no. H6143.
- 7. For details of standard reasons for apparently idle road works, refer to the "List of Standard Reasons for Idle Site" (which may be downloaded from Highways Department's web site). Otherwise it shall be approved by the Director of Highways.
- 8. The information of the display board shall be printed in English and Chinese and shall be clear and legible. Free-hand writing is not permitted.
- 9. For works not carried out by Highways Department,
 - (a) the telephone no. shall be replaced by a telephone no. manned 24 hours by "the promoter of the works" to answer any enquiries or complaints; and
- (b) the name and logo shall be replaced by the name and/or logo of "the promoter of the works"*. Note 10 to Note 14 Applicable to drawing no. H6133 Only:

10. Size of lettering:

	English				Chinese				Number		
Height	18	12	10	8	7	54	28	14	12	30	18
Width	14	10	8	6	6	54	28	14	12	24	14

- 11. The display board shall be displayed at a prominent location and orientated towards pedestrians for the public's reference.
- 12. For a work site (including decked areas) less than 50 metres in length, one display board shall be provided. For a work site (including decked areas) longer than 50 metres in length, display boards shall be provided at the ends of the site and along the site at a maximum spacing of 50 metres.
- 13. The display board shall be securely mounted on a stable structure (e.g. temporary barrier, hoarding or railing).
- 14. Using plastic backing plate instead of aluminium backing plate is permitted. The face of the plastic display board shall not show signs of deterioration, such as cracking, scaling, blistering, delamination and corrosion.

Note 15 to Note 18 Applicable to drawing no. H6138 Only:

- 15. For details of the display board support, refer to drawing nos. H6165, H6166 and H6167.
- 16. For guidelines on the provision of display boards for motorists explaining reasons for idle sites, refer to the current revision of Highways Department's Guidance Notes No. RD/GN/024 (which may be downloaded from Highways Department's website).
- 17. The face of the insert plates shall be constructed in retroreflective materials conforming to "Class RA1" of BS EN 12899-1.
- 18. Size of lettering:

		English			Chinese					Number		
He	ight	55	45	35	27	120	70	45	38	35	120	55
Wi	dth	44	36	28	22	120	70	45	38	35	96	44

1	Note 3 and 17 revised	signed	Jul 20
Н	Note 7 and 16 revised	-	Feb 15
G	Note 15 revised	-	Jul 12
F	Note 7 revised	-	Oct 10
E	Drawing title amended and minor revision on lettering heights	-	Mar 10
D	Drawing title and notes revised.	-	Jan 07
С	Size of lettering added and Note 6 revised.	-	Jul 05
В	General revision	-	Aug 03
Α	General revision	-	Nov 02
•	New Issue	-	Mar 97
REF.	REVISION	SIGNATURE	DATE

* "the promoter of the works" may be
(i) the Permittee of an Excavation Permit or

(ii) the Permittee of an Expressway Permit.

DISPLAY BOARD FOR EXPLAINING REASONS FOR IDLE ROAD WORKS (SHEET 2 OF 3)

UТ	${\tt GHW}$	「AVC	DEP A	ו שם ו	A D M T
ПГ	чпи	AYS	D \mathbf{L} \mathbf{L} \mathbf{L}	I I I I I	исии

REFERENCE	DRAWING NO.	CAD
SCALE N.T.S.	H 6134	[